

Laserworld CS-3000 micro

Specially designed for semi-professional use, the **Laserworld CS-3000 micro** is an **analog-modulated RGB diode laser** with an output of **2'500 mW**. The system is designed for projecting laser effects such as beams, waves, and tunnels, and can also display basic graphics. It is computer controllable via ILDA, but can also be used with DMX, in sound-to-light mode, stand alone operation, or in master-slave configuration.

The Laserworld CS-3000 micro is an excellent choice for small- to medium-sized clubs, indoor events, and mobile DJ applications. Professional users can significantly expand the control options by using the external **ShowNET** interface and conveniently integrate the **Laserworld CS-3000 micro** into existing setups or workflows.

- 2'500 mW guaranteed power
- Graphics capable - 25 kpps @ 8°
- Max. scan angle 30°
- Full colour mixing - analog modulation
- Extremely sharp, intense beams – ca. 5 mm / 1.2 mrad
- Save safety settings directly to the laser; these apply in all modes
- Link multiple units with Power linking, DMX, and ILDA
- Free computer control software – Showeditor - upgradable to Showcontroller
- Multiple control modes - Auto, DMX, ArtNet, and ILDA



TECHNICAL DETAILS

Guaranteed Power at aperture	2'500 mW
Power Red	500 mW / 638 nm
Power Green	700 mW / 520 nm
Power Blue	1'800 mW / 450 nm
Beam Specifications	ca. 5 mm / 1.2 mrad
Scanner	25 kpps @ 8°
Max. Scan Angle	30°
Operation Modes	ILDA, DMX, S2L
Laser Class	4

Laser Source	Diode
Basic Patterns	ca. 130 (layers, tunnels, fences, waves, etc.)
Accessories	power cable, manual, interlock, key
Power Supply	85 V - 250 V / AC, 50/60 Hz
Power Consumption	40 W
Dimensions	200 x 165 x 141 mm (L x W x H)
Weight	3.0 kg
EAN / MPN	7640144995829



*Due to Advanced Optical Correction technology used in our laser systems the optical power of each colour within installed laser module(s) may slightly differ from the specification of respective laser module(s). Divergence FWHM average depending on model.