

Laserworld CS-3000 micro

Specially designed for semi-professional use, the **Laserworld CS-3000 micro** is an **analog-modulated RGB diode laser** with an output of **2'500 mW**. The system is designed for projecting laser effects such as beams, waves, and tunnels, and can also display basic graphics. It is computer controllable via ILDA, but can also be used with DMX, in sound-to-light mode, stand alone operation, or in master-slave configuration.

The Laserworld CS-3000 micro is an excellent choice for small- to medium-sized clubs, indoor events, and mobile DJ applications. Professional users can significantly expand the control options by using the external **ShowNET** interface and conveniently integrate the **Laserworld CS-3000 micro** into existing setups or workflows.



- 2'500 mW guaranteed power
- Graphics capable - 25 kpps @ 8°
- Max. scan angle 30°
- Full color mixing - analog modulation
- Extremely sharp, intense beams - ca. 5 mm / 1.2 mrad
- Link multiple units with Power linking, DMX, and ILDA
- Multiple control modes - Sound-to-light, Auto, DMX, and ILDA

TECHNICAL DETAILS

Guaranteed Power at aperture	2'500 mW	Laser Source	Diode
Power Red	500 mW / 638 nm	Basic Patterns	ca. 130 (layers, tunnels, fences, waves, etc.)
Power Green	700 mW / 520 nm	Accessories	power cable, manual, interlock, key
Power Blue	1'800 mW / 450 nm	Power Supply	85 V - 250 V / AC, 50/60 Hz
Beam Specifications	ca. 5 mm / 1.2 mrad	Power Consumption	40 W
Scanner	25 kpps @ 8°	Dimensions	200 x 165 x 141 mm (L x W x H)
Max. Scan Angle	30°	Weight	3.0 kg
Operation Modes	ILDA, DMX, S2L	EAN / MPN	7640144995829
Laser Class	4		



*Due to Advanced Optical Correction technology used in our laser systems the optical power of each colour within installed laser module(s) may slightly differ from the specification of respective laser module(s). Divergence FWHM average depending on model.