

## Laserworld CS-3000 micro

Specially designed for semi-professional use, the **Laserworld CS-3000 micro** is an **analog-modulated RGB diode laser** with an output of **2'500 mW**. The system is designed for projecting laser effects such as beams, waves, and tunnels, and can also display basic graphics. It is computer controllable via ILDA, but can also be used with DMX, in sound-to-light mode, stand alone operation, or in master-slave configuration.

The Laserworld CS-3000 micro is an excellent choice for small- to medium-sized clubs, indoor events, and mobile DJ applications. Professional users can significantly expand the control options by using the external **ShowNET** interface and conveniently integrate the **Laserworld CS-3000 micro** into existing setups or workflows.

- 2'500 mW guaranteed power
- Graphics capable - 25 kpps @ 8°
- Max. scan angle 30°
- Full color mixing - analog modulation
- Extremely sharp, intense beams - ca. 5 mm / 1.2 mrad
- Link multiple units with Power linking, DMX, and ILDA
- Multiple control modes - Sound-to-light, Auto, DMX, and ILDA



### TECHNICAL DETAILS

<b>Guaranteed Power at aperture</b>	2'500 mW
<b>Power Red</b>	500 mW / 638 nm
<b>Power Green</b>	700 mW / 520 nm
<b>Power Blue</b>	1'800 mW / 450 nm
<b>Beam Specifications</b>	ca. 5 mm / 1.2 mrad
<b>Scanner</b>	25 kpps @ 8°
<b>Max. Scan Angle</b>	30°
<b>Operation Modes</b>	ILDA, DMX, S2L
<b>Laser Class</b>	4

<b>Laser Source</b>	Diode
<b>Basic Patterns</b>	ca. 130 (layers, tunnels, fences, waves, etc.)
<b>Accessories</b>	power cable, manual, interlock, key
<b>Power Supply</b>	85 V - 250 V / AC, 50/60 Hz
<b>Power Consumption</b>	40 W
<b>Dimensions</b>	200 x 165 x 141 mm (L x W x H)
<b>Weight</b>	3.0 kg
<b>EAN / MPN</b>	7640144995829



\*Due to Advanced Optical Correction technology used in our laser systems the optical power of each colour within installed laser module(s) may slightly differ from the specification of respective laser module(s). Divergence FWHM average depending on model.