Laserworld CS-6000 micro



Specifically built for semi-professional use, the **Laserworld CS-6000 micro** is an analog-modulated **RGB diode laser** delivering an output of **5'800 mW**. The system is designed for laser effects such as beams, waves, and tunnels, and can also display basic graphics. For versatile operation, integrated ILDA and DMX interfaces are provided, alongside plug-and-play functions, sound-to-light, stand-alone, and master-slave modes. This unit is an ideal solution for medium-sized clubs, indoor events, and mobile DJ applications.
Professional users can significantly expand the control options by using the external **ShowNET** interface and conveniently integrate the **Laserworld CS-6000 micro** into existing setups or workflows.

- 5'800 mW guaranteed power
- Graphics capable - 30 kpps @ 8°
- Max. scan angle 50°
- Full colour mixing - analog modulation
- Extremely sharp, intense beams – ca. 5 mm / 1.2 mrad
- Link multiple units with Power linking, DMX, and ILDA
- Multiple control modes - Sound-to-light, Auto, DMX, and ILDA

TECHNICAL DETAILS

Guaranteed Power at aperture	5'800 mW
Power Red	950 mW / 638 nm
Power Green	1'500 mW / 520 nm
Power Blue	4000 mW / 450 nm
Beam Specifications	ca. 5 mm / 1.2 mrad
Scanner	30 kpps @ 8°
Max. Scan Angle	50°
Operation Modes	ILDA, DMX, S2L
Laser Class	4

Laser Source	Diode
Basic Patterns	ca. 130 (layers, tunnels, fences, waves, etc.)
Accessories	power cable, manual, interlock, key
Power Supply	85 V - 250 V / AC, 50/60 Hz
Power Consumption	50 W
Dimensions	230 x 210 x 142 mm (L x W x H)
Weight	5.0 kg
EAN / MPN	7640144995836



*Due to Advanced Optical Correction technology used in our laser systems the optical power of each colour within installed laser module(s) may slightly differ from the specification of respective laser module(s). Divergence FWHM average depending on model.