

## Laserworld PL-10 FB4

The latest generation of Purelight **IP65** laser systems features innovative **RSL2 technology**, which combines an extremely compact and lightweight design with outstanding beam quality. With **9'800 mW** of power and an IP65 rating, the **Laserworld PL-10 FB4** is a dependable choice for large-scale club installations, touring and production, and medium-sized outdoor shows. Its **45 kpps @ 8°** scanning system ensures it is fully capable of handling professional graphics projections.

Each device features an integrated FB4 mainboard and a built-in color display for easy operation mode configuration. This hardware allows the Purelight Series to be controlled directly via various laser software or integrated into lighting setups via **DMX and Art-Net**.



- RSL2 module, optimized optical performance and a more compact housing
- Graphics capable – 45 kpps @ 8°
- Maximum scan angle: 50°
- Full color mixing – analog modulation
- Sharp, intense beams – ca. 5.5 mm
- IP65 waterproof housing
- Save safety settings directly to the laser (applies in all modes)
- Link multiple units with Power, DMX, and ILDA linking
- Multiple control modes: Auto, DMX, Art-Net, and ILDA
- Including waterproof flightcase
- Integrated Pangolin FB4 interface

### TECHNICAL DETAILS

<b>Guaranteed Power at aperture</b>	9'800 mW
<b>Power Red</b>	3'000 mW / 638 nm
<b>Power Green</b>	2'800 mW / 520 nm
<b>Power Blue</b>	5'000 mW / 450 nm
<b>Beam Specifications</b>	ca. 5.5 mm / 0.9 mrad
<b>Scanner</b>	45 kpps @ 8°
<b>Max. Scan Angle</b>	50°
<b>Operation Modes</b>	FB4, ILDA, DMX
<b>Laser Class</b>	4

<b>Laser Source</b>	Diode
<b>Basic Patterns</b>	Available for download
<b>Accessories</b>	Incl. waterproof flightcase, power cable, manual, interlock, key
<b>Power Supply</b>	85 V - 250 V / AC, 50/60 Hz
<b>Power Consumption</b>	120 W
<b>Dimensions</b>	313 x 200 x 212 mm (L x W x H)
<b>Weight</b>	14
<b>EAN / MPN</b>	7640144998479FB4



\*Due to Advanced Optical Correction technology used in our laser systems the optical power of each colour within installed laser module(s) may slightly differ from the specification of respective laser module(s). Divergence FWHM average depending on model.