

Laserworld PL-70

The latest generation of Purelight **IP65** laser systems features innovative **RSL2 technology**, which combines an extremely compact and lightweight design with outstanding beam quality. Delivering **70'000 mW** of power and featuring an IP65 rating, the **Laserworld PL-70** is a great choice for the most demanding large-scale club installations, touring and production, and even the largest outdoor shows. Its **30 kpps @ 8°** scanning system ensures it is fully capable of handling complex graphics projections. Each device features an integrated ShowNET mainboard and a built-in color display for easy operation mode configuration. This powerful hardware allows the Purelight Series to be controlled directly via LAN connection using various laser software or integrated into professional lighting setups via **DMX and Art-Net**.



- Innovative RSL2 module technology for optimized optical performance and a compact housing
- Min. power at aperture: 70'000 mW
- Professional graphics capable – 30 kpps @ 8°
- Max. scan angle: 50°
- Sharp, intense beams – ca. 10 mm
- IP65 waterproof housing – ideal for heavy-duty outdoor use
- Save safety settings directly to the ShowNET mainboard
- Link multiple units with Power, DMX, and ILDA linking
- Free computer control software (Showeditor) included – upgradable to Showcontroller
- Multiple control modes: Auto, DMX, Art-Net, and ILDA
- Built-in display for easy selection of operating modes
- Including waterproof flightcase

ShowNET mainboard as standard:

- Various control options:

TECHNICAL DETAILS

Guaranteed Power at aperture	70'000 mW	Laser Source	Diode
Power Red	23'000 mW / 638 nm	Basic Patterns	over 120 (level, tunnel, grid, waves, etc.)
Power Green	28'000 mW / 520 nm	Accessories	Incl. waterproof flightcase, power cable, manual, interlock, key, full version Showeditor software license included
Power Blue	28'000 mW / 450 nm	Power Supply	85 V - 250 V / AC, 50/60 Hz
Beam Specifications	ca. 10 mm / 1.1 mrad	Power Consumption	800 W
Scanner	30 kpps @ 8°	Dimensions	480 x 360 x 290 mm (L x W x H)
Max. Scan Angle	50°	Weight	50 kg
Operation Modes	ILDA, DMX, Art-Net, LAN, ILDA streaming, integrated SD card, stand-alone	EAN / MPN	7640144998547
Laser Class	4		



*Due to Advanced Optical Correction technology used in our laser systems the optical power of each colour within installed laser module(s) may slightly differ from the specification of respective laser module(s). Divergence FWHM average depending on model.