

## tarm 6 (1 pc)

**NEW. Including durable plastic case with some signs of usage.**

The tarm 6 (1 pc) is the perfect all-rounder for professional users and lighting designers. With built-in multi-control mainboard for **DMX, ArtNET, LAN, ILDA, ILDA streaming, stand-alone operation, etc.** Fast scanners for professional graphics projections, mappings and other installation projects. The tarm 6 (1 pc) has a rugged, compact chassis, making it ideal for **professional shows and rental companies.**

- 6'000 mW guaranteed power
- Quality graphics capable - 45kpps @ 8° scanners
- Extremely sharp intense beams - low divergence of <0.6 mrad
- Full color mixing
- Integrated powerful mainboard with advanced configuration features (geo-correction, zone setup, color balancing, etc.) and DAC feature
- Integrated network switch for linking the control signal
- Control screen for convenient mode selection
- Rugged tour grade compact housing
- **Laser Artists' choice**
- **Lighting Designers' choice**
- incl. durable plastic case



ShowNET mainboard as standard:

- Various control options:

### TECHNICAL DETAILS

<b>Guaranteed Power at aperture</b>	6'000 mW	<b>Laser Source</b>	Diode
<b>Power Red</b>	2'000 mW / 637 nm	<b>IP rating</b>	IP54
<b>Power Green</b>	1'800 mW / 520 nm	<b>Basic Patterns</b>	over 120 (layers, tunnels, fences, waves, etc.)
<b>Power Blue</b>	3'200 mW / 450 nm	<b>Accessories</b>	Incl. PVC Case, power cable, manual, key, interlock connector, full version Showeditor software (V1.2) license included
<b>Beam Specifications</b>	ca. 4.5 mm / <0.6 mrad	<b>Power Supply</b>	85 V - 250 V / AC
<b>Scanner</b>	45kpps @ 8°	<b>Power Consumption</b>	230 W
<b>Max. Scan Angle</b>	50°	<b>Dimensions</b>	320/260/140 mm
<b>Operation Modes</b>	ILDA, DMX, LAN, ArtNet, integrated SD card, stand-alone, master-slave; integrated intelligent ShowNET laser mainboard with display	<b>Weight</b>	13 kg
<b>Laser Class</b>	4	<b>EAN / MPN</b>	R93661_t6



\*Due to Advanced Optical Correction technology used in our laser systems the optical power of each colour within installed laser module(s) may slightly differ from the specification of respective laser module(s). Divergence FWHM average depending on model.