

## tarm 6 (21 pcs)

Only 21 pcs available (price per unit)

NEW

The tarm 6 (21 pcs) is the perfect all-rounder for professional users and lighting designers. With built-in multi-control mainboard for DMX, ArtNET, LAN, ILDA, ILDA streaming, stand-alone operation, etc.. Fast scanners for professional graphics projections, mappings and other installation projects. The tarm 6 (21 pcs) has a rugged, compact chassis, making it ideal for professional shows and rental companies.



- 6'000 mW guaranteed power
- Quality graphics capable - 45kpps @ 8° scanners
- Extremely sharp intense beams - low divergence of <0.6 mrad
- Full color mixing
- Integrated powerful mainboard with advanced configuration features (geo-correction, zone setup, color balancing, etc.) and DAC feature
- Integrated network switch for linking the control signal
- Control screen for convenient mode selection
- Rugged tour grade compact housing
- Laser Artists choice
- Lighting Designers choice
- incl. durable plastic case

ShowNET mainboard as standard:

- Various control options:

### TECHNICAL DETAILS

<b>Guaranteed Power at aperture</b>	6'000 mW	<b>Basic Patterns</b>	over 120 (layers, tunnels, fences, waves, etc.)
<b>Power Red</b>	2'000 mW / 637nm	<b>Accessories</b>	Incl. waterproof flightcase, raincover power cable, manual, key, interlock connector, full version Showeditor software license included
<b>Power Green</b>	2'000 mW / 520nm	<b>Power Supply</b>	85 V - 250 V / AC
<b>Power Blue</b>	2'500 mW / 450nm	<b>Power Consumption</b>	230W
<b>Beam Specifications</b>	ca. 4.5 mm / <0.6 mrad	<b>Dimensions</b>	320 x 260 x 140 mm
<b>Scanner</b>	45kpps @ 8°	<b>Weight</b>	12.4
<b>Max. Scan Angle</b>	50°	<b>EAN / MPN</b>	R93952
<b>Operation Modes</b>	ILDA, DMX, LAN, ArtNet, integrated SD card, stand-alone, master-slave; integrated intelligent ShowNET laser mainboard with display		
<b>Laser Class</b>	4		



\*Due to Advanced Optical Correction technology used in our laser systems the optical power of each colour within installed laser module(s) may slightly differ from the specification of respective laser module(s). Divergence FWHM average depending on model.